

# 45 WATT AC-DC CONVERTER VTB-00B SERIES

## General Description

VT is the basic series of switching power supplies manufactured by ETA Electric Industry. 188 different models are available. Output power ranges from 10W to 600W. 50 models have dual outputs; 33 models are designed with triple outputs. Input selectable ("SZ") models conform to local power conditions.

## Features

Compact

Isolated outputs

High Performance and Reliability

Excellent for equipment/din rail applications



Specifications<AC/DC>												Model																											
VTB**B 45WATTS /3 OUTPUTS				VTB01B			VTB01B-B			VTB03B			VTB04B																										
<b>Input Characteristic</b>																																							
Input Voltage												AC200V(DC260V)																											
Input Range												AC180-264V(DC220-350V)																											
Input Frequency												50/60Hz																											
Input Frequency Range												47-440Hz																											
Phase												Single																											
Inrush Current *1												25A(maximum) at rated input/output																											
Efficiency [%] (typical) *2												78	81	78	79																								
<b>Output Characteristic</b>																																							
Output Voltage [V]		5	+12	-12	+12	+5	-12	5	+12	-5	5	+15	-15																										
Output Current [A]		5.0	0.83	0.83	3.0	1.0	0.4	5.0	0.83	0.83	5.0	0.65	0.65																										
at horizontal mount 25W		5.0	1.0	0.5	3.0	1.0	0.4	5.0	1.0	0.83	5.0	0.65	0.65																										
at vertical mount 30W		-	-	-	4.0	-	-	-	-	-	-	-	-																										
peak current																																							
Voltage Adjust Range		V1:+5% of Rated Output Voltage(at no load within input range)												V2,V3:fixed with tolerance of +/-3.5% Rate Output Voltage(at no load within input range)																									
Ripple and Noise [mVp-p](maximum) *3		100	170	170	170	100	170	100	170	100	100	200	200																										
Regulation																																							
a.Statistic Line Regulation [mV](maximum)		35	84	84	84	35	84	35	84	35	35	105	105																										
b.Statistic Load Regulation [mV](maximum)		50	120	120	120	50	120	50	120	50	50	150	150																										
c.Temperature Coefficient *4		0.03%/°C																																					
d.Drift[mV](maximum) *5		40	75	75	75	40	75	40	75	40	40	90	90																										
e.Dynamic Load Regulation [mV](typical) *6		150	360	360	360	150	360	150	360	150	150	450	450																										
f.Recovery Time *6		0.5mS(typical)																																					
Rise up time		200mS(maximum) at 25°C and rated input/output																																					
Hold up time		18mS(minimum) at 45W at 25°C and rated input/output																																					
<b>Functions</b>																																							
Overcurrent Protection		Current Limiting with automatic recovery																																					
Overvoltage Protection		Zener diode clamping																																					
Remote Sense		not available																																					
Remote On/Off		not available																																					
<b>Environmental</b>																																							
Operating Temperature		0 to +50°C																																					
Operating Humidity		85%RH(non-condensing)																																					
Storage Temperature		-20 to +85°C																																					
Storage Humidity		30 to 85%RH(non-condensing)																																					
Withstanding Voltage		Primary-Secondary AC2,500V for 1minute																																					
		Primary-Frame Ground AC2,500V for 1minute																																					
		Secondary-Frame Ground AC500V for 1minute																																					
Isolation Resistance		Primary-Secondary-Frame Ground 50MΩ(minimum) by DC500V insulation tester																																					
Vibration		5-10Hz:10mm double amplitude,10-55Hz:19.6m/s <sup>2</sup> ,20minutes' period for 60minutes each along X,Y,Z axes(non-operating)																																					
Shock		294m/s <sup>2</sup>																																					
Cooling		Convection																																					
? Leakage Current		1.0mA(maximum)																																					
? Line Conduction Noise		Not specified																																					
? Safety		-																																					
? Weight (typical)		470g																																					
? MTBF [H]		420,000																																					
? Switching Frequency[kHz](typical)		43																																					