



## ETO-SX SERIES

Model	Output		Efficiency
ETO24SX	24V	166A	85%
ETO26SX	26V	154A	85%
ETO28SX	28V	142A	85%
ETO48SX	48V	83A	85%
ETO200SX	200V	20A	85%

### DESCRIPTION

The High Power PFC isolated Front Ends provide 24, 26, 28 and 48VDC single output. Complete front-end solutions for driving high density DC to DC modules in distributed Power Systems with (N+1) redundancy. Meeting international safety and EMI standards, this ET series provides high reliable and rugged compact power with DMTBF over 500,000 hours.

### FEATURES

- Power Factor (>0.99)
- 0 C to +50 C at full load
- Standard 5" X 5" X 15.50" envelope
- Output Fully Floating
- Overcurrent Protection
- Overvoltage Protection
- Remote Sense
- Overtemperature Protection
- Self-contained Forced Air Cooling
- Meets UL, CSA and VDE Safety
- Meets EMI EN88155 Level A ISO9001 (1997)

### OPTIONS

- Hot Pluggable
- Wide Temp Operation
- Power Fall Signal
- Logic Inhibit
- Single Wire Current Sharing
- Power Good Single
- Diode Isolation
- Output Current monitor

### ELECTRICAL SPECIFICATIONS

#### INPUTS

RANGE: Full input Range 180 to 264 VAC.  
 FREQUENCY: 43 to 63Hz.  
 INRUSH CURRENT: 25A averaged over ½ cycle  
 HARMONIC CURRENT: <5%  
 EFFICIENCY: 80% to 85% (Measured at full load and 208 VAC Input)

#### OUTPUTS

VOLTAGE: See Table  
 CURRENT: See Table  
 ADJUSTMENT RANGE: +/-10% of nominal output voltage.  
 POLARITY: Output is isolated. It may be referenced plus/minus as required.  
 REMOTE SENSING: Compensates for up to 0.5V total loop drop in the output line.  
 STATIC REGULATION: Line: +/- 0.25% over full line range.  
 Load: Option: +/-% zero load to full load. Droop IFE: Option: the output sags from +5% when the load is increased from 10% to 100%.  
 VOLTAGE STABILITY: +/-0.1% FOR 24 hour period after 30 minute warm up.  
 OUTPUTS  
 TEMP COEFFICIENT: +/-0.02%/ C FROM 0 c TO +50 c. For Wide Temperature. Option: +/- 0.035%/ C from -30 C to +70 C.  
 P-P RIPPLE AND NOISE: 1% (20Hz to 50MHz Bandwidth).  
 MINIMUM LOAD: Not Required.  
 TURN ON DELAY: 1 sec. Max from application of AC line.  
 OVER VOLTAGE PROTECTION: 125% +/-5% of nominal. OVP shutdown is latched until the input line is removed for 5 secs and then reapplied. OVP sensing is don at the output terminals.  
 OVERCURRENT PROTECTION: Current I=Limit Point: 110% to 120% of full load.

# ETO-SX SERIES

## ENVIRONMENTAL

### OVERTEMPERATURE PROTECTION:

Automatically shuts down and latches the unit in the event of an over temperature condition. After cool down, power must be recycled to restart the unit.

**AUDIBLE NOISE:** 63 dBA max at 1 meter. 70 dBA for high speed fans. (See Output Tables for units with high speed fan).

**TEMPERATURE:** Standard: 0 C to +50 C at full load. Storage: -55 C to +85 C.

**HUMIDITY:** 20% to 95% non-condensing.

**ALTITUDE:** Operating: 5,000 Ft. Derates to 85% at 10,000 Ft. Non-Operating at 30,000 feet.

**VIBRATION:** Operating: From 5 to 27Hz, 0.02" double amplitude: from 27 to 500Hz, 0.75G, 3 Axes, 5 min/octave sweep, dwell 1 min at resonance.

**Non-Operating:** From 5 to 17Hz, 0.01" double amplitude: from 17 to 500Hz, 1.5G peak: 3 axes, 5min/octave sweep, dwell 1 min at resonance.

**MTBF:** 500,000 hours

**SHOCK:** Operating: 5G, half sine, 11msec 3 axes. Non-Operating: 15G half sine, 11 msec, 3 axes.

**COOLING:** Forced air, internal fan Airflow normally exits at connector.

**EMI:** Conducted & Radiated EN55022 level A

**SAFETY:** Meets UL1950 , CSA1950, and TUV t EN60950. Factory is an approved BABT manufacturer.

## DIMENSIONS:

Weight: 14.8 lbs.

